



SKYLIGHT COVER INSTALLATION: (Just 3 easy steps)

1. Turn your SHAADS® cover over to see the back where the magnets are located.
 2. Center your SHAADS® Cover to the skylight cavity/opening, good side to the sheetrock so magnets are facing you. Mark the center of all 4 magnets, 2 on each side, at the edge of the ceiling no more than 1/8" up from ceiling edge, "see fig 1".
 3. Where you made these 4 marks place the bottom of the bracket on the mark at edge of ceiling (again no more up from the edge than 1/8") "Fig 2". Make sure hole of bracket is on top into the cavity at the edge of the ceiling then make a mark through the hole as to where the screw goes. Screw all 4 brackets into the inside walls/cavity of the skylight "see fig 2".
- Turn the cover to where the magnets are facing the brackets. Now place the magnets of your New SHAADS® Cover onto the bottom 2 brackets and lift the cover to the top 2 "L" brackets. Make small adjustment. **YOU ARE DONE !!!**

REMOVAL: When removing for cleaning of the cover, carefully place your hands at the two top corners or at the two bottom corners of the SHAADS® Cover pull away slowly from the brackets until all magnets release.

RE-INSTALL: the same way. Place magnets onto the bottom 2 brackets first then lift cover up to the 2 top "L" brackets.

NOTE: The SHAADS® Cover can be cut smaller to fit slightly inside the skylight cavity should you choose this look? "You must let us know before placing your order." With this request remember to adjust all brackets higher equally inside the cavity. When you received your new cover test your cover inside the cavity first to see how it fits. Skylight will vary in measurements be sure to measure each SKYLIGHT separately. SHAADS® Company will not be responsible for mis-measuring.